

Type	Specification	Features Description	Photo
LD-AS1701	<p>Three-dimensional automatic lock screw machine</p> <p>Applicable screw diameter : M1.5~6.0mm Applicable screw length : Max 25mm-60mm (by screw size) Route range X/Y/Z(mm):500 / 500 / 100 (can also be produced as needed) Drive mode : precision closed loop step Positioning accuracy : ±0.02mm The maximum load of the table :8KG Lock cast speed : 1.3S/1PCS Sequential storage : support 200 products Control system : PLC+ touch screen control system/ embedded motion controller Screw handling mode : vacuum suction / blowing style Screw supply : independent research and development Electric group : kellett speed Power Supply: AC 220V 50/60HZ Power: 300W Required Air Pressure: 0.5Mpa Dimensions : about 550*500*550(all sizes are availabe) Net Weight: 55Kgs</p>	<p>All the aluminum alloy professional mold profiles to build, the appearance of the atmosphere thick, single power grant, duplex bit, product pick and place time with the lock time parallel, the highest efficiency, support the pre-process into/behind the process out, to achieve low-cost unattended operation; speed than the same industry equipment, the average level of about 20% faster, less than 1.3 seconds / screw; can automatically lock all kinds of screws, its automatic function, simply put the product into by hand. such as: electronic PCB board, 3C products, toys, electronic products..... and other lock screw fixed work.</p>	