


Type	Specification	Features Description	Photo
LD-AS1801	Three-dimensional automatic Dispensing machine		
	Route range X/Y/Z(mm):500 / 500 / 100 (can also be produced as needed) Drive mode : precision closed loop step Positioning accuracy : $\pm 0.02\text{mm}$ The maximum load of the table :8KG Dispensing speed : 1S-2S/1PCS Sequential storage : support 200 products Control system : PLC+ touch screen control system / embedded motion controller Dispensing mode : pressure Dispensing controller + plastic tip : indepenent research and development Power Supply: AC 220V 50/60HZ Power: 300W Required Air Pressure: 0.5Mpa Dimensions : about 550*500*550 (all sizes are available) Net Weight: 45Kgs	Applicable Dispensing products : mobile phone keys 、 integrated circuits 、 printed circuit boards 、 LCD screen 、 electronic components 、 medical equipment 、 chassis bonding 、 optical lens 、 mechanical parts, etc... 1 、 with a draw, line, arc, circle, irregular curve continuous tween input program and other functions and three-dimensional dispensing ; 2 、 any point, line, surface, arc and other irregular curve continuous dispensing function; 3 、 high-speed, low noise precision stepper motor to make dispensing better; 4 、 dispensing force automatic compensation function, so that the operation more convenient; 5 、 XY area array, translation rotation operation function, anti-use tray, for different work positioning.	